

WELDOX 700

2008-01-17

Minimum length: 2000 mm

Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100,0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

The table shows available dimensions for direct order including the maximum length (m)

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

WIDTH [mm]	1000-	-1351	-1500	-1601	-1701	-1801	-1901	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301	
[mm]	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3,0-3,7																						
(3,7)-4,7*																						
(4,7)-5,7																						
(5,7)-6,7																						
(6,7)-7,7																						
(7,7)-8,7																						
(8,7)-10																						
(10)-24																						
(24)-25																						
(25)-26																						14,4
(26)-27	14																				14,2	13,8
(27)-28	13,4																				14,2	13,7
(28)-29	13																				14,1	13,3
(29)-30	12,5																				14,1	12,9
(30)-31	12,1																				13,6	12,4
(31)-32	11,8																				13,2	12
(32)-33	11,4																				12,8	11,7
(33)-34	11,1																				12,4	11,3
(34)-35	10,7																				12	11
(35)-36	10,4																				11,7	10,7
(36)-37	10,2																				11,3	10,5
(37)-38	9,9																				11,1	10,2
(38)-39	9,6																				10,8	10
(39)-40	9,4																				10,5	9,7
(40)-45	8,3																				10,2	9,5
(45)-50	7,5	13,5	13,5	13,5	13,5	13,4	14,1	13,4	12,8	12,3	11,7	11,3	10,8	10,4	10,1	9,7	10,9	10,6	10,2	9,9	9,6	8,4
(50)-55	6,8	11,2	11,2	11,2	11,2	11,2	11,2	11	10,5	10	9,6	9,2	8,9	8,5	8,2	8,7	8,4	8,2	8,2	8,2	8,2	7,6
(55)-60	7,8	11,2	11,2	11,2	11,2	11,1	10,6	10,1	9,6	9,2	8,8	8,4	8,1	7,8	7,5	7,9	7,7	7,4	7,4	7,4	7,4	6,9
(60)-65	7,2	11,2	11,2	11,2	10,8	10,3	9,7	9,3	8,9	8,5	8,1	7,8	7,5	7,2	6,9	6,7	6,5	6,3	6,3	6,3	6,3	6,3
(65)-70	6,7	10,8	10,8	10,7	10,1	9,5	9	8,6	8,2	7,9	7,5	7,2	6,9	6,7	6,4	6,2						
(70)-75	6,2	10,1	10,1	10	9,4	8,9	8,4	8	7,7	7,3	7	6,7	6,5	6,2								
(75)-80	5,9	9,4	9,4	9,3	8,8	8,3	7,9	7,5	7,2	6,9	6,6	6,3										
(80) - 102		7,4	7,4	7,3	7	6,7	6,3	6	5,7	5,5	5,3	5										
(102) - 115		6,5	6,5	6,5	6	5,8	5,5	5,2	5	4,8	4,6	4,4										
(115) - 130		5,8	5,8	5,7	5,4	5,1	4,8	4,6	4,4	4,2	4	3,9										

* 4,0 - 4,7 mm thickness available in some dimensions through stock. Contact your Stock coordinator for more information

